



Excalibur Crossbow String & Brace Height Guide

Crossbow	Length	Strands	Serving	Material	Part #	Brace
MICRO 315, 355, Suppressor, New MICRO 335	26 1/8"	28	Angel Majesty 036	Dynaflight 97 or Brownell D75	1993	1.5"-2"
MICRO 335 (older 3 degree version)	26 1/8"	28	Angel Majesty 036	Dynaflight 97 or Brownell D75	1993	1"-1.5"
Bulldog 400, Bulldog 380	31 1/8"	28	Angel Majesty 036	Dynaflight 97 or Brownell D75	1992	1.5"-2"
MATRIX Grizzly, GRZ2, Cub	31 1/8"	28	Angel Majesty 036	Dynaflight 97 or Brownell D75	1992	1"-1.5"
MATRIX Series (405, 400, 380, 355, 330, 310)	31 1/8"	28	Angel Majesty 036	Dynaflight 97 or Brownell D75	1992	.5"-1"
EXO TRADITIONAL Series Mag-Tip Limbs (Equinox, Exomax, Exomag Vortex, Exocet, Vixen, Axiom, Ibex, Phoenix, Eclipse)	35 1/2"	32	Angel Majesty 036	Brownell B50 Dacron OR Dynaflight 97 Flemish	1994 1989	.5"-1"
EXO TRADITIONAL Series Carved-Tip Limbs -(Exocet, Exomag, Exomax, Vixen, Wolverine)	35 1/2"	32	Angel Majesty 036	Brownell B50 Dacron	2010	.5"-1"

Note: Brace height is measured from the joint where the riser meets the rail. The string should never touch the suppressor pads if it does adjustments can be made by simply twisting it counter clockwise until the correct brace height is achieved. You can't over-twist the string. If the brace height is slightly more than stated it is still OK to use and will stretch with use.

